

PRO SP FULLY SYNTHETIC

Gasoline Engine Oil

Product Description

PRO Series is an advanced fully synthetic engine oil, formulated with 100% Group III base stocks and next-generation additive technology, meeting API SP / ILSAC GF-6 standards.

It provides outstanding protection against wear, oxidation, and Low-Speed Pre-Ignition (LSPI), ensuring longer engine life, cleaner pistons, and improved fuel efficiency.

Performance Features & Benefits

- Fully synthetic formulation ensures maximum engine cleanliness and durability
- Protects against LSPI, oxidation, and high-temperature deposits
- Excellent low-temperature fluidity for rapid cold starts
- Improved fuel economy and reduced emissions

Applications

- Designed for modern gasoline engines
- Suitable for vehicles requiring API SP, SN Plus, SN, SM, SL or equivalent
- Compatible with hybrid and stop-start systems
- Recommended for all-season use in passenger cars, SUVs, and light commercial vehicles

Typical Characteristics

Property	Test Method	SAE 5W-30	SAE 10W-40
Kinematic Viscosity @ 40°C	ASTM D445	62 cSt	94 cSt
Kinematic Viscosity @ 100°C	ASTM D445	10.5 cSt	14.5 cSt
Viscosity Index	ASTM D2270	160	155
Density @ 15°C	ASTM D1298	0.855 g/cm ³	0.865 g/cm ³
Flash Point (COC)	ASTM D92	230°C	232°C
Pour Point	ASTM D97	-42°C	-36°C
Total Base Number (TBN)	ASTM D2896	8 mg KOH/g	8
Noack Volatility	ASTM D5800	<10%	>10%
Sulfated Ash wt%	ASTM D874	0.8	0.8

Specifications & Approvals

- API SP / SN Plus / SN - ILSAC GF-6A / GF-5 - ACEA A5/B5, A3/B4
- MB 229.5 / VW 502 00 / 505 00 / BMW LL-01 - Renault RN0700 / RN0710

Unit No.G114-Small And Medium Complexes-SC
 District 6 Million-10TH Of Ramadan Al sharqia Egypt
 +20116577730 / +20112511858
 info@spikelube.co

