

# DX III ATF FULLY SYNTHETIC

## AUTOMATIC TRANSMISSION FLUID

### Product Description

DX III Fully Synthetic is a premium automatic transmission fluid, formulated from advanced synthetic base oils and high-performance additives.

It provides exceptional thermal and oxidation stability, along with precise friction control for smooth and reliable performance.

### Performance Features & Benefits

- Fully synthetic formulation – ensures long-lasting oxidation and thermal stability
- Smooth and consistent shifting across all operating temperatures
- Outstanding low-temperature fluidity – quick lubrication and easy cold starts
- Excellent anti-wear & anti-foam protection – extends transmission life

### Applications

- Recommended for automatic transmissions requiring DEXRON III(H), DEXRON II(E), or MERCON performance
- Suitable for power steering systems, hydraulic systems, and torque converters

### Typical Characteristics

| Property                          | Test Method | Result                  |
|-----------------------------------|-------------|-------------------------|
| Kinematic Viscosity @ 40°C        | ASTM D445   | 34 cSt                  |
| Kinematic Viscosity @ 100°C       | ASTM D445   | 7.2 cSt                 |
| Viscosity Index                   | ASTM D2270  | 195                     |
| Density @ 15°C                    | ASTM D1298  | 0.855 g/cm <sup>3</sup> |
| Flash Point (COC)                 | ASTM D92    | 215°C                   |
| Pour Point                        | ASTM D97    | -43°C                   |
| Brookfield Viscosity @ -40°C (cP) | ASTM D2983  | <18,000                 |

### Specifications & Approvals

Meets or exceeds:

- GM DEXRON III(H)
- Ford MERCON
- Allison C-4

